



PCTWORLD INTELLECTUAL PROPERTY ORGANIZATION
International Bureau

INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(51) International Patent Classification ⁶ : H02K 29/03, D06F 37/30	A1	(11) International Publication Number: WO 98/00902 (43) International Publication Date: 8 January 1998 (08.01.98)
(21) International Application Number: PCT/SI97/00021 (22) International Filing Date: 2 July 1997 (02.07.97) (30) Priority Data: P-9600209 2 July 1996 (02.07.96) SI P-9700153 9 June 1997 (09.06.97) SI (71) Applicant (for all designated States except US): DOMEL ELEKTROMOTORJI IN GOSPODINJSKI APARATI, D.O.O. [SI/SI]; Otoki 21, 4228 Železniki (SI). (72) Inventors; and (75) Inventors/Applicants (for US only): DOLENC, Sandi [SI/SI]; Log 58, 4228 Železniki (SI). JELENC, Janko [SI/SI]; Dašnica 55, 4228 Železniki (SI). (74) Agent: PIPAN, Marjan; Kotnikova 5, 1000 Ljubljana (SI).		(81) Designated States: AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, CA, CH, CN, CU, CZ, DE, DK, EE, ES, FI, GB, GE, GH, HU, IL, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MD, MG, MK, MN, MW, MX, NO, NZ, PL, PT, RO, RU, SD, SE, SG, SK, SL, TJ, TM, TR, TT, UA, UG, US, UZ, VN, YU, ZW, European patent (AT, BE, CH, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE). Published <i>With international search report. Before the expiration of the time limit for amending the claims and to be republished in the event of the receipt of amendments.</i>
(54) Title: ELECTRONICALLY COMMUTATED MOTOR FOR DIRECT DRIVE OF WASHING MACHINE DRUM		
 		
(57) Abstract <p>The invention concerns an electronically commutated motor for direct drive of a washing machine drum, wherein the rotor (2) is fixed directly to the driving shaft of the drum, with the stator (1) being fixed to the cross-shaped support of the drum. The structure of an electronically commutated motor for direct drive of a washign machine drum makes it possible, through an optimal stator pole (6)/intermediate space (10) width ratio, and with an uneven air gap (8) between the stator (1) and the rotor (2), to achieve a low noise level and a relatively high moment at the motor shaft. The number of rotor poles represented by magnetic segments (3) is greater than the number of stator poles (6) with coils (4), the rotor poles/stator poles ratio factor equalling 1.3333, and the stator pole (6)/intermediate space (19) width ratio between the stator poles (6) equalling 1.868.</p>		

FOR THE PURPOSES OF INFORMATION ONLY

Codes used to identify States party to the PCT on the front pages of pamphlets publishing international applications under the PCT.

AL	Albania	ES	Spain	LS	Lesotho	SI	Slovenia
AM	Armenia	FI	Finland	LT	Lithuania	SK	Slovakia
AT	Austria	FR	France	LU	Luxembourg	SN	Senegal
AU	Australia	GA	Gabon	LV	Latvia	SZ	Swaziland
AZ	Azerbaijan	GB	United Kingdom	MC	Monaco	TD	Chad
BA	Bosnia and Herzegovina	GE	Georgia	MD	Republic of Moldova	TG	Togo
BB	Barbados	GH	Ghana	MG	Madagascar	TJ	Tajikistan
BE	Belgium	GN	Guinea	MK	The former Yugoslav Republic of Macedonia	TM	Turkmenistan
BF	Burkina Faso	GR	Greece	ML	Mali	TR	Turkey
BG	Bulgaria	HU	Hungary	MN	Mongolia	TT	Trinidad and Tobago
BJ	Benin	IE	Ireland	MR	Mauritania	UA	Ukraine
BR	Brazil	IL	Israel	MW	Malawi	UG	Uganda
BY	Belarus	IS	Iceland	MX	Mexico	US	United States of America
CA	Canada	IT	Italy	NE	Niger	UZ	Uzbekistan
CF	Central African Republic	JP	Japan	NL	Netherlands	VN	Viet Nam
CG	Congo	KE	Kenya	NO	Norway	YU	Yugoslavia
CH	Switzerland	KG	Kyrgyzstan	NZ	New Zealand	ZW	Zimbabwe
CI	Côte d'Ivoire	KP	Democratic People's Republic of Korea	PL	Poland		
CM	Cameroon	KR	Republic of Korea	PT	Portugal		
CN	China	KZ	Kazakhstan	RO	Romania		
CU	Cuba	LC	Saint Lucia	RU	Russian Federation		
CZ	Czech Republic	LI	Liechtenstein	SD	Sudan		
DE	Germany	LK	Sri Lanka	SE	Sweden		
DK	Denmark	LR	Liberia	SG	Singapore		
EE	Estonia						

5

**ELECTRONICALLY COMMUTATED MOTOR FOR DIRECT DRIVE OF
WASHING MACHINE DRUM**

10

15 The invention concerns an electronically commutated motor for direct drive of a washing machine drum, wherein the rotor is fixed directly to the driving axle of the drum, and the stator is fixed to the cross-shaped support of the drum. The invention belongs to the IPC class H02K 7/00.

20 The technical problem, which has been successfully solved by the present invention, is how to build a driving motor for a washing machine drum that will provide direct drum driving at low noise levels and a relatively high moment at the motor shaft.

Washing machines widely use asynchronous or universal collector motors for driving the drum, which are installed under the drum. Power transfer from the motor to the drum is carried out by way of two pulleys and a belt with the usual gear ratio of 1:12. The described arrangement
5 has several drawbacks: high counterweight mass due to motor position outside the drum centre; high level of noise, particularly during the centrifuging stage; relatively short life expectancy of the belt; motor characteristic is unadapted to the load characteristic; and low yield of the drive.

10 All the above-mentioned drawbacks are eliminated through the design of a washing machine with direct drive of the drum. The stator of such motor is fixed to the cross-shaped support of the drum, whereas the rotor is mounted directly onto the driving axle of the washing drum. Thus the motor itself thus has no bearing of its own, as it uses the existing drum
15 bearing instead. In such a structure of the drive, the prior art two driving pulleys and the belt are no longer necessary, which means a considerable reduction of counterweight. In addition to the above-mentioned advantages, a direct drive also eliminates the previously enumerated drawbacks of the conventional drive of washing machine drums.

20 Motor versions have been known for direct drive of washing machines, which are usually equipped with a number of stator poles greater than that of rotor poles, resulting in strong pulsations of the shaft moment, and consequently, in a high noise level. The air gap between the rotor and the

stator is usually even, this providing an inter-phase induced voltage of trapezoidal form, which - at the usual current form - again leads to a relatively high noise level. An optimal stator pole/intermediary space width ratio should be chosen in order to obtain a low noise level and a relatively high moment at the machine shaft. In prior art direct drives this ratio is not optimal. With the conventional method of producing laminations, where the external and internal motor diameters are relatively large, there is a large quantity of scrap, which results in higher production costs of the motor. The prior art drives also use the conventional way of front and groove insulation, which is a time- and money-consuming process.

The structure of an electronically commutated motor for direct drive of a washing machine drum in accordance with the invention makes it possible - through an optimal stator pole/intermediate space width ratio and with an uneven air gap between the stator and the rotor - to obtain a low noise level and a relatively high moment at the motor shaft.

An electronically commutated motor for direct drive of a washing machine drum in accordance with the invention will now be described by way of example and with reference to the accompanying drawings in which:

20

Figure 1 is a cross-sectional view illustrating a rotor and stator part;

Figure 2 illustrates a stator assembly segment of a motor in accordance with the invention;

Figure 3 illustrates a stator and motor part of a motor in accordance with the invention showing uneven air gaps;

5 **Figure 4** illustrates the production of a stator lamination;

Figure 5 is a schematic presentation of different electrical connections of a motor for the different working operations of a washing machine;

10 **Figure 6** is a longitudinal cross-sectional view illustrating a motor in accordance with the invention;

Figure 7 illustrates the magnetization of magnetic segments;

Figure 8 illustrates stator poles.

An electronically commutated motor for direct drive of a washing
15 machine drum in accordance with the invention comprises a stator 1 consisting of a stator assembly made of dynamo sheet including a stator frame 5 with stator poles 6 expressed along its periphery. Coils 4 are installed on said expressed stator poles 6, which represent a concentric three-phase stator winding. A rotor 2 of the motor is carried out as a soft-
20 magnetic iron core 7 onto which magnetic segments 3 are bonded.

The stator 1 of an electronically commutated motor in accordance with the invention is fixed to the cross-shaped support of the washing machine. The number of rotor poles represented by said magnetic segments 3 is

greater than the number of the expressed stator poles 6, the rotor poles/stator poles ratio factor equalling 1.3333.

An uneven air gap between the rotor and stator poles can be achieved in two ways. In the first case, the magnetic segments 3 of rectangular form are bonded to the rotor core 7, with the upper surface of the stator poles 9 in the stator assembly 12 having a slightly convex shape, thus producing an uneven air gap 8. In the second case, the magnetic segments 3 can be shaped according to the radius, with the stator poles 9 being straight. Through an uneven air gap thus formed between the stator and the rotor, a sinusoidal form of the inter-phase induced voltage is obtained which strongly reduces the noise level during motor operation. The stator pole 9/intermediate space 10 width ratio between the individual stator poles 9 equals 1.868. Such a ratio represents an optimal choice, since minimal turning moment pulsation is achieved through it along with a minimal noise level.

A schematic presentation of electrical connections of the motor for the different washing machine operations is shown in Figure 4. The three-phase motor winding 19 is star connected, with each phase having two taps: one for washing and one for the centrifuge. During the washing cycle, when lower rotational speed is needed, the motor is connected between terminals U1, V1 and W1. In this case the entire winding is active. During centrifuging, when high rotational speed is needed, the motor is connected between terminals U2, V2 and W2. In this position

only a part of the winding is active. The centrifuging/washing ratio of the active winding can be 1:3, 1:4 or 1:5. Said winding 19 with taps makes it possible for the motor to operate under optimal conditions through all washing cycles.

5 Figure 4 illustrates a part of production of a stator assembly. Individual stator laminations are cut out of a strip 11 and then formed by bending the cut-out strip to a pre-determined diameter. Two stator assemblies can be simultaneously cut out of the strip 11. The cut-out strips for the first stator assembly are bent in one direction, and those for the second assembly
10 are bent in the other direction. Simultaneously with the stator laminations also auxiliary grooves 13 are cut out of the strip, which will facilitate subsequent bending of the cut-out strip to the pre-determined diameter.

 The stator assembly itself is lined with plastic material which forms front insulation 14, groove insulation 15 and a hub 16 for the fixation of the
15 stator to the cross-shaped support of the drum.

 On the plastic lining of the stator assembly, places are provided for the fixation of circuits 17 of Hall generators - three in number - which lie in the centre of adjacent grooves, at an angular distance of 15° with regard to each other. The position of the circuits 17 is shown in Figure 1.

20 The magnetic segments 3 together with the iron core are also lined with plastic material 18 which, in addition to fixing the magnetic segments 3 to the iron core 7, also forms a hub for the fixation of the rotor 2 to the shaft of the washing machine drum.

Additional reduction of moment pulsations and thereby the reduction of noise are achieved through magnetization of magnetic segments 20 into a delta form, as shown in Figure 7, or by shaping stator poles 21 into a double trapezoidal form, as shown in Figure 8.

- 5 An electronically commutated motor for direct drive of a washing machine drum in accordance with the invention has successfully solved the set technical problem of direct drive of a washing machine drum with minimum moment pulsation and hence, with a low noise level and a relatively high moment at the motor shaft. In addition, the described
- 10 structural solution of a motor also provides the possibility of easy, large-series production.

CLAIMS

1. An electronically commutated motor for direct drive of a washing machine drum, wherein a stator (1) is fixed to the cross-shaped support of the washing machine and a rotor (2) is fixed directly to the axle of the washing machine drum,

characterised in that

the number of rotor poles represented by magnetic segments (3) is greater than the number of stator poles (6) with coils (4), the stator poles/rotor poles ratio factor being 1.3333, whereas the stator pole (6) intermediary space (10) width ratio between said stator poles (6) is 1.868.

2. An electronically commutated motor for direct drive of a washing machine drum as claimed in Claim 1,

characterised in that

said magnetic segments (3) bonded to the rotor core (7) have a rectangular form, with the upper surface of stator poles (9) in a stator assembly (12) being slightly convex, thus forming an uneven air gap (8).

3. An electronically commutated motor for direct drive of a washing machine drum as claimed in Claim 1,

characterised in that

said magnetic segments (3) are shaped according to the radius, while
said stator poles (9) are straight.

- 5 4. An electronically commutated motor for direct drive of a washing
machine drum as claimed in Claims 1 to 3,

characterised in that

a three-phase winding (19) is star connected, with each phase having
two taps, whereby in the first regime, the motor is connected between
10 the terminals U1, V1 and W1 with the entire winding being active, and
in the second regime, the motor is connected between the terminals
U2, V2 and W2, with a part of the winding being active, the ratio of the
active windings between the first and the second regime being 1:3, 1:4
or 1:5.

15

5. An electronically commutated motor for direct drive of a washing
machine drum as claimed in Claims 1 to 4,

characterised in that

a stator assembly (12) is made by cutting stator laminations out of a
20 strip (11), whereupon the stator assembly (12) is formed by bending the
cut-out strip (11) to a pre-determined diameter.

6. An electronically commutated motor for direct drive of a washing machine drum as claimed in Claim 5,

characterised in that

two stator assemblies (12) are simultaneously cut out of a strip (11)
5 and formed by bending the cut-out strip (11) in one direction for the first assembly, and into another for the second assembly.

7. An electronically commutated motor for direct drive of a washing machine drum as claimed in Claims 5 and 6,

10 **characterised in that**

simultaneously with said stator laminations auxiliary grooves (13) are cut out of said strip (11).

8. An electronically commutated motor for direct drive of a washing machine drum as claimed in Claims 1 to 7,

15

characterised in that

said stator assembly (12) is lined with plastic material, this forming front insulation (14), groove insulation (15) and a hub (16) for the fixation of the stator (1) to the cross-shaped support of the drum.

20

9. An electronically commutated motor for direct drive of a washing machine drum as claimed in Claims 1 to 8,

characterised in that

in the plastic lining of the stator assembly fixation places are provided for three circuits (17) of Hall generators lying in the centre between the adjacent grooves (10) at an angular distance of 15° with regard to each other.

5

10. An electronically commutated motor for direct drive of a washing machine drum as claimed in Claims 1 to 9,

characterised in that

10 said magnetic segments (3) together with the iron core (7) are lined with plastic material (18), which at the same time forms a hub for the fixation of the rotor (2) to the shaft of the washing machine drum.

11. An electronically commutated motor for direct drive of a washing machine drum as claimed in Claims 1 to 10,

15

characterised in that

magnetic segments (20) are magnetized to form a delta, whereas the stator poles are straight.

12. An electronically commutated motor for direct drive of a washing machine drum as claimed in Claims 1 to 10,

20

characterised in that

stator poles (21) are formed into a double trapezoidal form, whereas the magnetic segments are magnetized in a straight line.

1/7




FIGURE 1




FIGURE 2




FIGURE 3




FIGURE 4




FIGURE 5




FIGURE 6

7/7




FIGURE 7




FIGURE 8

INTERNATIONAL SEARCH REPORT

International Application No

PCT/SI 97/00021

A. CLASSIFICATION OF SUBJECT MATTER

IPC 6 H02K29/03 D06F37/30

According to International Patent Classification (IPC) or to both national classification and IPC

B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)

IPC 6 H02K D06F

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

Electronic data base consulted during the international search (name of data base and, where practical, search terms used)

C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category *	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
A	US 5 030 864 A (VAN HOUT HENRICUS M ET AL) 9 July 1991 see column 2, line 6 - column 3, line 6 ---	1
A	DE 39 41 709 A (PHILIPS PATENTVERWALTUNG) 20 June 1991 see column 1, line 10 - column 2, line 47 ---	1
A	US 3 860 843 A (KAWASAKI ITARU ET AL) 14 January 1975 see column 2, line 13 - line 20; claims 1-7 ---	1-3
A	US 4 712 035 A (FORBES FRANKLIN L ET AL) 8 December 1987 see figures 2,3,22 --- -/--	4-7

☒ Further documents are listed in the continuation of box C.

☒ Patent family members are listed in annex.

* Special categories of cited documents:

"A" document defining the general state of the art which is not considered to be of particular relevance

"E" earlier document but published on or after the international filing date

"L" document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)

"O" document referring to an oral disclosure, use, exhibition or other means

"P" document published prior to the international filing date but later than the priority date claimed

"T" later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention

"X" document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone

"Y" document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art.

"&" document member of the same patent family

2

Date of the actual completion of the international search	Date of mailing of the international search report
4 November 1997	10/11/1997
Name and mailing address of the ISA European Patent Office, P.B. 5818 Patentlaan 2 NL - 2280 HV Rijswijk Tel. (+31-70) 340-2040. Tx. 31 651 epo nl. Fax: (+31-70) 340-3016	Authorized officer Wansing, A

INTERNATIONAL SEARCH REPORT

International Application No

PCT/SI 97/00021

C.(Continuation) DOCUMENTS CONSIDERED TO BE RELEVANT

Category	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
A	PATENT ABSTRACTS OF JAPAN vol. 014, no. 200 (E-0920), 24 April 1990 & JP 02 041641 A (HITACHI LTD), 9 February 1990, -----	5-7
A	US 5 489 811 A (KERN ROBERT ET AL) 6 February 1996 see figures 3,4 -----	5
A	EP 0 421 346 A (DAIKIN IND LTD) 10 April 1991 see figure 5 -----	9
A	US 4 626 727 A (JANSON JAN) 2 December 1986 see figure 4 -----	9

INTERNATIONAL SEARCH REPORT

Information on patent family members

International Application No

PCT/SI 97/00021

Patent document cited in search report	Publication date	Patent family member(s)	Publication date
US 5030864 A	09-07-91	NL 8801700 A DE 3921725 A FR 2635927 A GB 2220529 A.B	01-02-90 11-01-90 02-03-90 10-01-90
DE 3941709 A	20-06-91	US 5099165 A	24-03-92
US 3860843 A	14-01-75	CA 934814 A DE 2132477 A FR 2099961 A GB 1354144 A NL 7108601 A.B	02-10-73 13-01-72 17-03-72 05-06-74 28-12-71
US 4712035 A	08-12-87	CA 1330882 A AU 603346 B AU 6509486 A AU 640987 B AU 7081791 A CA 1323650 A CA 1333007 A DE 3638228 A FR 2595019 A FR 2607158 A FR 2607157 A FR 2739633 A GB 2183932 A.B GB 2220681 A.B JP 62114456 A MX 174576 B MX 9206924 A US 4835839 A US 5619871 A	26-07-94 15-11-90 14-05-87 09-09-93 23-05-91 26-10-93 15-11-94 27-05-87 28-08-87 27-05-88 27-05-88 11-04-97 10-06-87 17-01-90 26-05-87 27-05-94 30-06-94 06-06-89 15-04-97
US 5489811 A	06-02-96	WO 9326077 A	23-12-93
EP 0421346 A	10-04-91	JP 3124249 A DE 69027172 D DE 69027172 T DE 69030452 D DE 69030452 T	27-05-91 04-07-96 28-11-96 15-05-97 28-08-97

INTERNATIONAL SEARCH REPORT

Information on patent family members

International Application No

PCT/SI 97/00021

Patent document cited in search report	Publication date	Patent family member(s)	Publication date
EP 0421346 A		EP 0627806 A	07-12-94
		US 5083052 A	21-01-92
<hr/>			
US 4626727 A	02-12-86	NL 8401519 A	02-12-85
		EP 0161032 A	13-11-85
		HK 83791 A	01-11-91
		JP 60245457 A	05-12-85
<hr/>			